


769 LR  
MALE ELBOW



**TUBE (METRIC) ISO TAPERED THREAD**

Ordering Information	A	T	D	W		N	E	N1	I
	Tube O.D.	(ISO)		Wrench Flat					
	mm	in	mm	in	mm	mm	mm	mm	mm
769LR _ 3 X 1/18	3	R-1/8	2.4	7/16	11.1	17.0	23.6	17.8	12.9
769LR _ 3 X 1/4	3	R-1/4	2.4	1/2	12.7	18.0	24.6	23.4	12.9
769LR _ 4 X 1/8	4	R-1/8	2.4	1/2	12.7	18.8	25.4	18.8	13.7
769LR _ 4 X 1/4	4	R-1/4	2.4	1/2	12.7	18.8	25.4	23.4	13.7
769LR _ 6 X 1/8	6	R-1/8	4.8	1/2	12.7	19.6	27.0	18.8	15.3
769LR _ 6 X 1/4	6	R-1/4	4.8	1/2	12.7	19.6	27.0	23.4	15.3
769LR _ 6 X 3/8	6	R-3/8	4.8	11/16	17.5	22.4	29.8	26.2	15.3
769LR _ 6 X 1/2	6	R-1/2	4.8	13/16	20.6	24.4	31.8	33.0	15.3
769LR _ 8 X 1/8	8	R-1/8	4.8	9/16	14.3	21.3	28.8	19.8	16.2
769LR _ 8 X 1/4	8	R-1/4	6.4	9/16	14.3	21.3	28.8	24.4	16.2
769LR _ 8 X 3/8	8	R-3/8	6.4	11/16	17.5	23.1	30.6	26.2	16.2
769LR _ 8 X 1/2	8	R-1/2	6.4	13/16	20.6	25.1	32.6	33.0	16.2
769LR _ 10 X 1/8	10	R-1/8	4.8	11/16	17.5	23.9	31.5	21.6	17.2
769LR _ 10 X 1/4	10	R-1/4	7.1	11/16	17.5	23.9	31.5	26.2	17.2
769LR _ 10 X 3/8	10	R-3/8	7.9	11/16	17.5	23.9	31.5	26.2	17.2
769LR _ 10 X 1/2	10	R-1/2	7.9	13/16	20.6	25.9	33.5	33.0	17.2
769LR _ 12 X 1/8	12	R-1/8	4.8	13/16	20.6	25.9	36.0	23.6	22.8
769LR _ 12 X 1/4	12	R-1/4	7.1	13/16	20.6	25.9	36.0	28.2	22.8
769LR _ 12 X 3/8	12	R-3/8	9.5	13/16	20.6	25.9	36.0	28.2	22.8
769LR _ 12 X 1/2	12	R-1/2	9.5	13/16	20.6	25.9	36.0	33.0	22.8
769LR _ 12 X 3/4	12	R-3/4	9.5	1 1/8	28.6	29.7	39.8	36.8	22.8
769LR _ 16 X 3/8	16	R-3/8	9.5	15/16	23.8	27.9	38.0	30.2	24.4
769LR _ 16 X 1/2	16	R-1/2	11.9	15/16	23.8	27.9	38.0	35.1	24.4
769LR _ 18 X 1/2	18	R-1/2	11.9	1 1/8	28.6	29.7	39.8	36.8	24.4
769LR _ 18 X 3/4	18	R-3/4	15.1	1 1/8	28.6	29.7	39.8	36.8	24.4
769LR _ 20 X 1/2	20	R-1/2	11.9	1 3/8	34.9	34.5	44.6	41.7	26.0
769LR _ 20 X 3/4	20	R-3/4	15.9	1 3/8	34.9	34.5	44.6	41.7	26.0
769LR _ 22 X 3/4	22	R-3/4	15.9	1 3/8	34.9	34.5	44.6	41.7	26.0
769LR _ 22 X 1	22	R -1	18.3	1 3/8	34.9	34.5	44.6	46.5	26.0
769LR _ 25 X 3/4	25	R-3/4	15.9	1 3/8	34.9	36.8	49.1	41.7	31.3
769LR _ 25 X 1	25	R -1	21.8	1 3/8	34.9	36.8	49.1	46.5	31.3

**Reference Specifications:**

- DIN - 2999
- BS - 21
- JIS - B0203
- ISO - 7/1-BSP-T

**Designation:**

Marking LR on Flat.

● "D" - Dimension is minimum opening. ● Dimensions are for reference only, and are subject to change without notice.